

The **Heirloom** ^{Collection} Handcrafted Wood Floors



Autumn Stone Walnut HC5AUTW



Bootstrap Maple HC5BTSM1



Buckskin Hickory HC5BUKH1



Jute Hickory HC5JUTH1



Morning Mist Maple



Natural Hickory HC5HICH1



Natural Walnut HC5NATW1



Shady Glen Maple HC5SHAM



Tea Leaf Hickory HC5TEAH1



Natural Walnut



Natural Hickory



Heirloom

Handcrafted Wood Floors

Benefits

Finish	True Mark - 9 coats of hardwearing Aluminum Oxide 100% Renewable w/ Warranty intact VOC Free Maintenance products Lifetime Finish Warranty
Structure	MG4 - 3 Guaranteed sanding's Highest possible stability w/ Solid Dry Sawn faces Guaranteed Third Party Certification
	Truecore - FSC certified Highest Green Certification Lifetime Structural Guarantee
Clean Air	CARB II - Surpasses standard by over 50%

Features

Length: Width:	Walnut & Hickory random uo to 6' or 7' Maple is random up to 6' 5"
Thickness:	9/16" 4mm sawn cut face Truecore Centerply
Surface Texture:	Medium Hand Sculpted
Edge Detail:	Handcrafted
Square Ft. per box:	17.5 sqft
Weight per box:	38 lbs
Warranty:	5 year commercial finish 10 year commercial structural

Lifetime residential finish Lifetime residential structural

Refer to www.hallmarkfloors.com for latest, updated information.



Color, Graining & Natural Changes

Wood is a natural product that features distinct color and graining. Each board is unique in its characteristics and will vary from piece to piece. The floor represents the natural visual characteristics of wood. Each board can vary from a clean to rustic visual and contain filled knots, sap wood, small filled splits and a high contrast within the natural and lighter stained visuals. These subtleties may become more distinct over time due to exposure to direct sunlight. Occasional rearranging of furniture and rugs will help reduce the potential affects of the sun.

Note: This sample may not be representative of your entire installed floor, for your reference and the latest updated information, please refer to www.hallmarkfloors.com to see our online room scenes and project galleries.

Maintenance

See Maintenance and Warranty Guide Carb II Compliant

Installation



Float





Over Radiant Heat [EXCLUDING HICKORY]

Glue Down

Installs over: concrete, wood, vinyl floors and radiant heat systems. Above, on or below grade. See complete installation instructions.

Trim Options

Stair Nose	Reducer
T-molding	Quarter Round
Threshold	

Hallmark Floors Inc 2360 S. Archibald Ave. Ontario, CA 91761 | 888.551.0888 | Fax 909.947.7776 | www.hallmarkfloors.com