



Pekoe, Oak



Ginseng Oak EOR567GINO



Marigold Oak EOR567MARO



Eucalyptus Leaf Oak EOR567EUCO



Pekoe Oak EOR567PEKO



Hibiscus Oak EOR567HIBO



Gunpowder Oak EOR567GUNO



Oolong Hickory EOR567OOLH



Darjeeling Hickory EOR567DARH



Chamomile Hickory EOR567CHAH



Chai Oak EOR567CHAO



Eucalyptus Leaf, Oak

## Features

Length:	Up to 6'2" RL
Width:	5, 6 & 7½" Random Width
Thickness:	5/8" Engineered 4mm Sawn Cut Face
Finish:	NuOil®
Edge Detail:	Handcrafted Bevel
Certified:	EPA – TSCA Title IV Complaint - Clean air Certified Renewable Sourcing
TrueCore:	Third Party Certified
Warranty:	Limited Lifetime residential finish Limited Lifetime residential structural 3 year commercial finish 10 year commercial structural
Maintenance:	Clean with NuOil® Floor Cleaner. For full care and maintenance instructions visit <a href="http://HallmarkFloors.com/Floor-Care-Maintenance">HallmarkFloors.com/Floor-Care-Maintenance</a>

## Benefits

Finish:	Protective low sheen - provides a truly natural wood floor Guaranteed quality and durability - long lasting finish 100% Renewable with Hallmark's Restoration Oil
Wear Layer:	Ultra thick wear layer provides lasting durability Same wear layer as 3/4" solid wood floors Easier to repair or touch up if an accident occurs
Structure:	Greater dimensional stability than 3/4" solid Healthy indoor air quality



Ginseng, Oak

## Trim Options

Stair Nose  
T-molding  
Threshold  
Reducer

## Installation



Nail Down



Glue Down



Float



Over Radiant Heat  
(Excluding Hickory)

Installs over: concrete, wood, vinyl floors and radiant heat systems. Above, on or below grade. See complete installation instructions. Hallmark Hickory and Solid products are not approved for installation over Radiant Heat.

## Fumed Characteristics

What to Expect with Fumed Floors



1. Regional Variation
2. Batch Variation
3. Plank Variation

Chai Oak, Gunpowder Oak, Pekoe Oak, Hibiscus Oak, Marigold Oak, Eucalyptus Leaf Oak, Ginseng Oak are Fumed.

Fuming simply deepens the natural colors and highlights the contrast of the wood planks without using stain to cover them. Our process creates a naturally richer, darker, clearer floor with a higher contrast of colors from board to board.

### What is Fumed Hardwood?

This is a natural accelerated aging process used to enhance the dark to light shades within every wood plank, batch & region. The deepening in color and variation is created by adding a natural oxidizing agent in a controlled environment to react with the naturally present tannins in the wood - Time, Temperature & Tannins (naturally present in the wood) mix to create one of a kind planks that we add to our Collections. While a very controlled environment and process, it is not 100% precise, every region, grove and tree produces individually unique high contrast color palette.

Learn more about the beauty of fuming,  
[www.hallmarkfloors.com/the-beauty-of-fumed-hardwood-floors/](http://www.hallmarkfloors.com/the-beauty-of-fumed-hardwood-floors/)

## Light Characteristics

Wood Floor Plank with Natural Finish  
Light\* Exposure Over 48 Months

New Installation			
			
			
12 Months Later	24 Months Later	48 Months Later	*All band widths

## Wood Characteristics

Color, Graining & Natural Changes



Wood flooring is a natural product that will feature distinct color and graining between planks. Each board contains large to small knots, sap wood, and a high contrast within the natural and lighter stained visuals. Knots and voids may or may not be filled with dark putty.

Note: This sample may not be representative of your entire installed floor, for your reference and the latest updated information, please refer to [hallmarkfloors.com](http://hallmarkfloors.com) to see our online room scenes and product galleries.

Before installation review the samples with the floor and verify our beautiful one of a kind floor is what you are expecting.

Installation constitutes acceptance.