



Sandbar Hickory



Mangrove Oak VE75MANO



Sandal Oak VE75SANO



Seashell Oak VE75SEAO




Marina Oak VE75MARO



Maritime Walnut VE75MARW



Tide Pool Maple VE75TIDM



Sand Castle Maple VE75SANM



Catamaran Hickory VE75CATH



Sandbar Hickory VE75SANH



Pearl Oak VE75PEAO



Catamaran Hickory

Features

- Length: Up to 6'2" RL
- Width: 7½"
- Thickness: 1/2" Engineered
2mm Slice Cut Face
- Finish: NuOil® (Oak)
TrueMark® Glaze Tek Poly (Maple & Hickory)
- Edge Detail: Handcrafted Microbevel
- Certified: EPA – TSCA Title IV Complaint - Clean air
Certified Renewable Sourcing
- TrueCore: Third Party Certified
- Warranty: Limited Lifetime residential finish
Limited Lifetime residential structural
3 year commercial finish (NuOil®)
5 year commercial finish (Glaze Tek)
10 year commercial structural
- Maintenance: Clean with NuOil® Floor Cleaner (Oak)
Clean with TrueClean Floor Cleaner (Maple & Hickory)
For full care and maintenance instructions visit
HallmarkFloors.com/Floor-Care-Maintenance

Benefits

- Finish: Protective low sheen - provides a truly natural wood floor (Oak)
Guaranteed quality and durability - long lasting finish
100% Renewable with Hallmark's Restoration Oil (Oak)
100% Renewable with Hallmark's XYZ (Maple & Hickory)
- Wear Layer: Same visuals as 3/4" solid wood floors
Top layer provides lasting durability
Vertically sliced - Delivers greater strength
- Structure: Greater dimensional stability than 3/4" solid
Healthy indoor air quality







Maritime Walnut

Trim Options

- Stair Nose
- T-molding
- Threshold
- Reducer

Installation

-  Nail Down
-  Glue Down
-  Float
-  Over Radiant Heat
(Excluding Hickory)

Installs over: concrete, wood, vinyl floors and radiant heat systems. Above, on or below grade. See complete installation instructions. Hallmark Hickory and Solid products are not approved for installation over Radiant Heat.

Fumed Characteristics

What to Expect with Fumed Floors



1. Regional Variation
2. Batch Variation
3. Plank Variation

Mangrove Oak, Sandal Oak, Seashell Oak, Marina Oak, Pearl Oak are Fumed.

Fuming simply deepens the natural colors and highlights the contrast of the wood planks without using stain to cover them. Our process creates a naturally richer, darker, clearer floor with a higher contrast of colors from board to board.

What is Fumed Hardwood?

This is a natural accelerated aging process used to enhance the dark to light shades within every wood plank, batch & region. The deepening in color and variation is created by adding a natural oxidizing agent in a controlled environment to react with the naturally present tannins in the wood – Time, Temperature & Tannins (naturally present in the wood) mix to create one of a kind planks that we add to our Collections. While a very controlled environment and process, it is not 100% precise, every region, grove and tree produces individually unique high contrast color palette.

Learn more about the beauty of fuming,
www.hallmarkfloors.com/the-beauty-of-fumed-hardwood-floors/

Light Characteristics

Wood Floor Plank with Natural Finish
Light* Exposure Over 48 Months

New Installation		
		
12 Months Later	24 Months Later	48 Months Later

*All band widths

Wood Characteristics

Color, Graining & Natural Changes



Wood flooring is a natural product that will feature distinct color and graining between planks. Each board contains large to small knots, sap wood, and a high contrast within the natural and lighter stained visuals. Knots and voids may or may not be filled with dark putty.

Note: This sample may not be representative of your entire installed floor, for your reference and the latest updated information, please refer to hallmarkfloors.com to see our online room scenes and product galleries.

Before installation review the samples with the floor and verify our beautiful one of a kind floor is what you are expecting.

Installation constitutes acceptance.